


Made in the
USA



11949 Westar Lane • Burlington, WA 98233
Toll: 877-757-7555 • Fax: 360-757-7567
info@usmower.com • www.usmower.com

The USM **EX60HDSS-BD SUPER SAMURAI** Belt Drive Shredder / Flail Mower is designed for excavators & backhoes in excess of 35,000 Lbs. w/ oil flows from 25 to 45 GPM needed in extreme conditions. The **EX60HDSS-BD** is manufactured w/ high strength 1/4" DOMEX 100,000 PSI Yield Strength Steel, 1/2 in. End Plates & 3/4" T-1 Stiffeners. The 5/8" wall **SUPER SAMURAI** Electronically Balanced Rotor Shaft is manufactured w/ towers that are 1/2" in thickness retaining (3) 2-Lb. Flail Knives and (1) 2-Lb. Thatch Knife attached w/ 1" Grade (8) Bolts, Castle Nut & Dowel Lock Pin. Cuts vegetation & trees up to 6" in diameter.



Pictured w/ optional High PSI
PISTON Motor



Made in the
USA



11949 Westar Lane • Burlington, WA 98233

Toll: 877-757-7555 • Fax: 360-757-7567

info@usmower.com • www.usmower.com

- ◆ 1/4" DOMEX 100,000 PSI Yield high strength steel construction
- ◆ 1/2" DOMEX End Plates & 3/4" T-1 End Plate Stiffeners
- ◆ 2 Lb. ea. x 8" Long x 3" wide x 10mm Thick Flail & Straight Thatch Knives
- ◆ Spiral blade configuration
- ◆ Gear type hydraulic motor (3000 PSI) matched to available oil flow
- ◆ **Optional 60CC PISTON Motor (5000 PSI) w/ 100" x 1/2" Case Line**
- ◆ 94 HP 4-Section Belt Drive System
- ◆ Polyester Powder Coat Finish, High Visibility Yellow
- ◆ Replaceable HARDOX Skid Shoes
- ◆ 12 month warranty
- ◆ 85" x 3/4" hydraulic hoses w/ 3/4" male flat face couplers
- ◆ 100" x 1/4" case drain line w/ 1/2" male flat face coupler
- ◆ Cutting Width 60"
- ◆ Weight 1,800 Lbs. w/o Mount
- ◆ Number of Flail Knives (36) 8" x 3" x 10mm x 2 Lbs. ea.
- ◆ Number of Thatch Knives (18) 8" x 3" x 10mm x 2 Lbs. ea.
- ◆ Flail Knife Mounting Towers 1/2 " in Thickness
- ◆ Cutting Capacity Up to 6" Diameter
- ◆ Aux. Hyd. Flow Required 25 GPM — 45 GPM
- ◆ Rotation speed 1800-2000 rpm
- ◆ Super Samurai Rotor Shaft 6" OD x 5/8" wall Electronically Balanced

