

Made in the
USA

US Mower
Creating Mowing Solutions



11949 Westar Lane
Burlington, WA 98233
877-757-7555
Fax: 360-757-7567
info@usmower.com
www.usmower.com



Single Gear Hydraulic Pump 'JAW-Coupling' No Lubrication required or
Optional variable load sense 40 GPM Piston pump @ 1800 ERPM



Made in the
USA

USMower
Creating Mowing Solutions



11949 Westar Lane
Burlington, WA 98233
877-757-7555
Fax: 360-757-7567
info@usmower.com
www.usmower.com



55,000 BTU Cooler w/ Fan
mounted to 25 gallon tank



Optional Electronic Joystick



USM Custom MFG Weight
No frame weights

Model (Flail Head)

Horizontal Reach Out From Mount:

Mowing Reach to Right Rear Tire:

MM19-50BF

19' 8"

1.0" to 6"

MM21-50BF

21' 2"

1.0" to 6"

MM22-50BF

22' 2"

1.0" to 6"

MM23-50BF

23' 2"

1.0" to 6"

Model (Rotary Head)

Horizontal Reach Out From Mount:

Mowing Reach to Right Rear Tire:

MM19-50URCM

19' 8"

1.0" to 6"

MM21-50URCM

21'

1.0" to 6"

MM23-60UREM

23' 6"

1.0" to 6"

Standard Hydraulic Power to Head:

Single Gear Pump 40 GPM @ 1800 ERPM

Optional Hydraulic Power to Head:

Variable Volume Load Sensing Piston Pump 40 GPM @ 1800 ERPM

Hydraulic Power Boom Functions:

On - Board Tractor Hydraulic System

Boom Function Controls:

Mechanical Cable Controls or Electronic Joystick Controls

Primary Excavator Boom Construction:

100,000 PSI Yield Strength **DOMEX** Steel

Secondary Jib Boom Construction:

100,000 PSI Yield Strength **DOMEX** Steel

Finish of Completed Unit:

Polyester Powder Coat — High Visibility Yellow

Head attachments:

40", 50" & 60" Brush Flails, 50" & 60" Rotary Heads, Ditcher

Warranty:

12 Months all models