

Made in the
USA

US Mower
Creating Mowing Solutions



11949 Westar Lane
Burlington, WA 98233
877-757-7555
Fax: 360-757-7567
info@usmower.com
www.usmower.com

Industry's 1st 23' Reach Premium Rear Cradle Boom Mower for 4wd Utility Class Tractors



- Superb Ground Clearance
- No Frame Weights
- Front Axle Stabilizer Cylinder
- Variable Load Sense Piston Pump
- 25 Gal Rear Hydraulic Tank
- 35,000 BTU Oil Cooler w/ Fan
- Electronic Joystick Controls
- 135° Mowing Swing Arc from Cradle



Made in the
USA



11949 Westar Lane
Burlington, WA 98233
877-757-7555
Fax: 360-757-7567
info@usmower.com
www.usmower.com

Industry's 1st 23' Reach Premium Rear Cradle Boom Mower for Utility Class Tractors

- | | |
|--|--|
| ◆ <u>135MM23P- 60UREM-H</u> | <u>Premium Rear Cradle Boom w/ 60" Rotary Brush Mower</u> |
| ◆ Primary Excavator Style Boom 9.75" x 7" DOMEX 100,000 PSI Yield Strength Steel | |
| ◆ Secondary Dipper Boom 6.75" x 6" DOMEX 100,000 PSI Yield Strength Steel | |
| ◆ Rear Cradle Boom Storage: | Standard |
| ◆ Front Axle Hydraulic Stabilizer: | Standard |
| ◆ Horizontal Boom Reach from Tractor Center Line: | 23' 4" |
| ◆ Reach up fully raised (18.4R30 Rear Tires): | 20' 9" |
| ◆ Minimum Reach Mower Head to Right Rear Tire: | 2" |
| ◆ Assembled Weight Less Ballasting: | 3,652 Lbs. |
| ◆ USM Custom MFG Wheel Weight: | 30" Rim 1963 Lbs. |
| ◆ Sugar Beat Juice Liquid Ballast Added @ Factory: | 30" Wheel 953 Lbs. |
| ◆ Variable Volume PISTON Hydraulic Pump: | 40.0 GPM @ 1800 RPM |
| ◆ 'Jaw Coupler' Pump Coupling, No Lubrication Required: | Standard |
| ◆ Tuck-A-Way 25 Gallon Hydraulic Tank, Provides Clear Operator Sight: | Standard |
| ◆ 35,000 BTU Oil Cooler w/ Fan Attached to Hydraulic Tank: | Standard |
| ◆ Electronic Joystick Control: | Standard |
| ◆ Full Rotation From Rear Cradle Stow Position: | 135 ° |
| ◆ Polyester Powder Coat Finish, High Visibility Yellow: | Standard |
| ◆ Vegetation Cutting Capacity (Rotary Head): | 8" |
| ◆ 12 Months Full Warranty: | Standard |

