

Made in the  
**USA**

**US Mower**  
Creating Mowing Solutions



11949 Westar Lane  
Burlington, WA 98233  
877-757-7555  
Fax: 360-757-7567  
info@usmower.com  
www.usmower.com

## 60RCM-H 60 in. HEAVY DUTY BOOM ROTARY MOWER HEAD



Made in the  
**USA**



11949 Westar Lane  
Burlington, WA 98233  
877-757-7555  
Fax: 360-757-7567  
info@usmower.com  
www.usmower.com

## **60RCM-H 60 in. HEAVY DUTY BOOM ROTARY MOWER HEAD**

Cutting width:	58 in. actual cut
Blade tip speed:	350 FPS @ 1400 RPM
Shroud super structure:	1/4 in. x 7.0 in. DOMEX
Shroud super structure center:	1/2 in. & 3/16 in x 10.0 in. DOMEX
Gear or Piston Motor:	Direct couple drive
Front hydraulic feeder gate:	Standard
Segmented HARDOX replaceable skid shoes:	Standard
Safety shielding: Full width 3/8 in. 2- ply neoprene belting:	Standard
Safety shielding: Single or double row chains:	Optional
Standard blade carrier:	2.0 in. x 6.0 in. x 42.0 in T- 1
Optional blade carrier:	1.0 in. x 42.0 in. T- 1
Double edge free swinging blades: 14.0 in long x 6.0 in wide x 5/8 in thick x 12.0 Lbs. ea.	Standard
Blade 4-square shank attachment bolts: 2.0 in x 3.0 in Grade 8	Standard
Continuous vegetation cutting capacity:	8.0 in. diameter
Operating Weight:	1,275 Lbs.
Polyester Powder Coat Finish, high visibility safety yellow:	Standard
Double HELAC Swivel:	Optional
12 Months Warranty:	Standard

