

Made in the  
**USA**

**USMower**  
Creating Mowing Solutions



11949 Westar Lane  
Burlington, WA 98233  
877-757-7555  
Fax: 360-757-7567  
info@usmower.com  
www.usmower.com

## **BD72BF– 72 in. BELT DRIVE BOOM BRUSH FLAIL MOWER**

Cutting width:	72 in.
Flail Knife speed:	188 Ft per second
Hood/shroud continuous form:	3/16 in. DOMEX
Cutter shaft drum wall thickness:	6.0 in. OD x 3/8 in
Hydraulic Rotor Shaft Gear Motor:	Belt Final Drive
Belt Drive Hydraulic Rotor Shaft Piston Motor:	Optional
Segmented HARDOX replaceable skid shoes front to back:	Standard
Curtains: Full width 3/8 in. 2- ply neoprene belting used as deflection shielding:	Standard
Hardened Edge Flail Knives: 5.5 in long x 2.5 in wide x .25 in thick x 15.0 oz. ea.	Standard
Flail Knife Attachment Bolts: .75 in x 4.0 in Grade 8	Standard
Continuous vegetation cutting capacity:	3.0 in. diameter
Rear Roller: 1/4 in. wall x 6-5/8 in. OD x 76.0 in length:	Standard
Rear Roller Stub Shaft Bearings:	(2) 1-7/16 in.
Operating Weight:	1,350 Lbs.
Polyester Powder Coat Finish, high visibility safety yellow:	Standard
Double HELAC Swivel:	Optional
12 Months Warranty:	Standard

